



Features & Benefits

- » Compact size perfect for limited space enclosures
- » UL Listed 1863
- » Versatile surface or DIN-Rail mount capability
- » Slide-hinged faceplate aids field termination
- » Patch or fusion splice field termination standard
- » Rugged metal construction with lifetime warranty

Product Description

Compact DIN-Rail or surface mount fiber optic patch panel. Compact size allows minimum space requirements within control cabinetry. Device includes splice trays to allow fusion splicing of field cabling (pigtailed sold separately). Device features a sliding faceplate with capture mechanism to allow patch panel to be kept open “hands-free”.

Product Variants

Part Number	External Interface	Internal Interface	Fiber Optic Wavelength
SNAPXL-24ST-MM	12ea. ST duplex connectors.	12ea. ST duplex connectors.	Multimode
SNAPXL-24ST-SM	12ea. ST duplex connectors.	12ea. ST duplex connectors.	Singlemode
SNAPXL-24ST-SC-MM	12ea. ST duplex connectors.	12ea. SC duplex connectors.	Multimode
SNAPXL-24ST-SC-SM	12ea. ST duplex connectors.	12ea. SC duplex connectors.	Singlemode
SNAPXL-24SC-MM	12ea. SC duplex connectors.	12ea. SC duplex connectors.	Multimode
SNAPXL-24SC-SM	12ea. SC duplex connectors.	12ea. SC duplex connectors.	Singlemode
SNAPXL-48LC-MM	12ea. LC quad connectors.	12ea. LC quad connectors.	Multimode
SNAPXL-48LC-SM	12ea. LC quad connectors.	12ea. LC quad connectors.	Singlemode

Custom fiber optic adapter variations are available via special order. Contact us.

Specifications

- Standards:** UL Listed 1863 (Communications-Circuit Accessories), CE
- Operating temperature:** -40°C to 75°C
- Storage/transport temperature:** -40°C to 80°C
- Relative humidity (non-condensing):** 10% to 95%
- Insertion Loss:** ≤.3dB (Multimode), ≤.2dB (Singlemode)
- Plug/Unplug Durability:** 1000 times

Mechanical Construction

- Dimensions with adapters installed:** (H x D x W) 7.75" x 5.75" x 3.5"
- Mounting Options:** Rear DIN-Rail, side DIN-Rail or surface mount
- Weight:** 2.3 lbs.
- Protection class:** IP20

Materials of Construction

- Patch panel body and faceplate:** 18 gauge powder-coat painted steel
- Fiber optic adapters:** UL 90 V-0 Thermoplastic
- Cable Glands:** Plastic with max. cable diameter of 12mm (14mm max. also available)

Warranty

Lifetime warranty on materials and workmanship.

Scope of Delivery and Accessories

Scope of delivery: Patch panel, DIN-Rail mounting adapter, 2ea. cable glands.

