


C104H/HS

4-port RS-232 ISA serial boards



PComm Lite

- > Cost-effective, compact ISA boards with 4 RS-232 ports
- > 921.6 Kbps maximum baudrate for super fast data transmission
- > 16-byte FIFO and on-chip H/W, S/W flow control
- > Drivers provided for Windows (2000/XP/2003/Vista/2008, 9X/ME/NT, 3.x), Windows XP Embedded, DOS, Linux 2.4, Linux 2.6 (x86/x64), QNX 4/6, FreeBSD 4/5, SCO OpenServer 5/6, UnixWare 7, Windows 7, Solaris 10 x86/x64
- > Easy configuration, without switches or jumpers



: Overview

The 4-port C104H/HS ISA boards offer users an economical, high performance multiport serial communication solution for connecting terminals, modems, printers, data acquisition equipment, and other serial devices to a PC. The boards are a top choice of industrial

automation engineers and system integrators, and support many different operating systems, including Windows, Linux, and even Unix. In addition, each of the 4 RS-232 ports supports a super fast 921.6 Kbps baudrate.

: Specifications

Hardware

Comm. Controller: 16C550C or compatible x 4
Bus: 16-bit ISA
Connector: DB37 female

Serial Interface

Number of Ports: 4
Serial Standards: RS-232
Max. No. of Boards per PC: 4

Serial Line Protection

ESD Protection: 25 KV on the board (C104HS only)

Performance

Baudrate: 50 bps to 921.6 Kbps

Serial Communication Parameters

Data Bits: 5, 6, 7, 8
Stop Bits: 1, 1.5, 2
Parity: None, Even, Odd, Space, Mark
I/O Address: 0x0000-0xFFFF (default = 0x180)
IRQ: 2 (9), 3, 4, 5, 7, 10 (default), 11, 12, 15

Serial Signals

RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND

Driver Support

Operating Systems: Windows 9X/ME/NT/2000, Windows XP/2003/Vista/2008/7 x86/x64, Windows 3.x, Windows XP Embedded, DOS, Linux 2.4, Linux 2.6 x86/x64, QNX 4/6, FreeBSD 4/5, SCO OpenServer 5/6, UnixWare 7, Solaris 10 x86/x64

Note: Please refer to Moxa's website for the latest driver support information.

Physical Characteristics

Dimensions: 83 x 157 mm (3.27 x 6.18 in)

Environmental Limits

Operating Temperature: 0 to 55°C (32 to 131°F)
Storage Temperature: -20 to 85°C (-4 to 185°F)
Ambient Relative Humidity: 5 to 95% (non-condensing)
Altitude: Up to 2000 m

Note: Please contact Moxa if you require products guaranteed to function properly at higher altitudes.

Standards and Certifications

EMC: CE, FCC
EMI: EN 55022, FCC Part 15 Subpart B Class A
EMS: EN 61000-4-2, EN 61000-4-3, EN 61000-4-4
Green Product: RoHS, CRoHS, WEEE

MTBF (mean time between failures)

Time: 629,545 hrs
Database: MIL-HDBK-217F, GB 25°C

Power Requirements

Power Consumption: 100 mA max. @ +5 V, 100 mA max. @ +12 V, 60 mA max. @ -12 V

Warranty

Warranty Period: 5 years
Details: See www.moxa.com/warranty

: Ordering Information

Available Models

C104H: 4-port RS-232 ISA serial board

C104H-DB9M: 4-port RS-232 ISA serial board (includes DB9 male cable)

C104H-DB25M: 4-port RS-232 ISA serial board (includes DB25 male cable)

C104HS: 4-port RS-232 ISA serial board with surge protection

C104HS-DB9M: 4-port RS-232 ISA serial board with surge protection (includes DB9 male cable)

C104HS-DB25M: 4-port RS-232 ISA serial board with surge protection (includes DB25 male cable)

Connection Options (can be purchased separately)

CBL-M37M9x4-30: DB37 male to DB9 male x 4 connection cable, 30 cm

CBL-M37M25x4-30: DB37 male to DB25 male x 4 connection cable, 30 cm

Package Checklist

- 1 C104H or C104HS board
- DB9 male or DB25 male connection cable
- Documentation and software CD
- Quick installation guide (printed)
- Warranty card